



Application/Uses

- Frozen food packaging
- Fresh food packaging
- Ice bags
- Heavy duty produce bags

Product Description

Westlake EF575AA resin is a fractional melt index 7.5% EVA copolymer designed for ice bags, frozen food bags, and other films that require excellent toughness and good heat sealing characteristics. This Kosher compliant resin has excellent low temperature brittleness properties.

Typical Physical Properties

Property		Test Method	Typical Value, Units
Melt Index		D 1238	0.55 g/10 min
*Density		D 1505	929 kg/m ³ (0.929 g/cm ³)
*Haze		D 1003	4.8%
*Specular Gloss @ 45°		D 2457	74
Dart Impact		D 1709	480 g (g/mil)
Ultimate Tensile	M.D.	D 882	3500 psi
	T.D.	D 882	3700 psi
Elongation	M.D.	D 882	380%
	T.D.	D 882	550%
1% Secant Modulus	M.D.	D 882	15,000 psi
	T.D.	D 882	16,000 psi

^a Unless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity.

^b Unless noted otherwise, the test method is ASTM.

^c Units are in SI or US customary units.

NOTES

Kosher Compliant. Test specimens for blown film: nominal thickness 1.25 mils; blow up ratio 2.5:1, die gap 35 mils. Experimental data – values are subject to change.

FDA

This resin grade complies with 21 CFR 177.1350. For further information, please contact Product Regulatory Compliance.

PROCESSING

Melt temperatures of 360° F – 400° F are recommended for Westlake Chemical EF575 with blow-up ratios of 1.5:1 or higher.

COMMENTS

Properties reported here are based on limited testing. Westlake makes no representation that the material in any particular shipment will conform exactly to the values given.

Westlake and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of any product, and nothing herein waives any of the Seller's conditions of sale.

WESTLAKE CHEMICAL CORPORATION
2801 Post Oak Blvd Suite 600 Houston, Texas
Customer Service: 1-800-545-9577